

When you are in need of refreshment, a nice glass of cold water is the best option. With the Animo OptiCool, you will always have fresh, cold and pure water at hand. Ideal for in the office, waiting rooms, sport centres, canteens, hotels, restaurants, hospitals...

FRESH, PURE AND COLD WATER

With the Animo OptiCool you can enjoy fresh, pure and cold water at every moment of the day. The OptiCool is a water cooler which you easily connect to the water system. Therefore you will never run out of water. Because the OptiCool is equipped with a direct cooling system, negative influences from the outside (such as bacteria) do not get the chance to affect the quality of the water. By the use of a water filter funny tastes, if any, will be removed and the flavour of water will be even more optimal. The OptiCool also means no more lifting of heavy bottles and no need to keep bottles in stock, which will save you costs and space.



OPTICOOL



OPTICOOL TS

SUMMARIZED



ALWAYS DELICIOUS, FRESH AND PURE WATER

- + Temperature adjustable between 2 and 12 °C
- + High quality / durability
- + Very compact and requires little space
- + Easy to install
- + Direct connection to the water system
- + Suitable for every situation
- + Low maintenance
- + No more lifting of heavy water bottles



WATER COOLER FOR JUGS

- + Especially for filling jugs, Animo has developed the OptiCool TS.
- This machine also has a plateau which makes it easy to dispense into glasses.



OPTIONS AND ACCESSORIES



EVERYTHING IS POSSIBLE

- + High quality water filter for optimal flavour
- + Base cabinet
- + Stand-alone set consisting of pump and water tank
- + Company-specific branding on door and / or side panels

MODEL	OptiCool	OptiCool TS
Article number	10445	10440
Dosing time	2.5 sec./glass	2.5 sec./glass
Hour capacity cold water *	approx. 10 litre (80 glasses of 120 ml.)	approx. 10 litre (80 glasses of 120 ml.)
Time before use	approx. 9 min.	approx. 9 min.
Temperature	2°C - 12°C	2°C - 12°C
Electrical connection	1N-230V/50Cy/225W	1N-230V/50Cy/225W
Water connection	3/4"	3/4"
Dimensions (W x D x H)	226 x 490 x 580 mm	226 x 490 x 580 mm
Dispensing height	118 mm	267 mm
Coolant	R134a	R134a
Min. water pressure	0,02 MPa (0,2 bar)	0,02 MPa (0,2 bar)
Max. water pressure	1 MPa (10 bar)	1 MPa (10 bar)
Weight (empty)	24,3 kg	24,3 kg
Weight (filled)	24,5 kg	24,5 kg

* inlet temperature 20°C

OPTICOOL AND OPTICOOL TS

All dimensions in millimeters.

