

The WKI range makes constant hot water always available. The water boilers of this range are meant for wall mounting, which makes them ideal for saving counter space. They are flexible in use. Water is drawn off as needed without loss of temperature.

BENEFITS



QUANTITY

- + Capacity 10, 20 and 40 litres
- + Large volumes can be supplied without any problems (flow 6 to 9 seconds per litre)
- + Level glass
- + On/off refill function



FEATURES


- + For wall mounting
- + Adjustable thermostat 0-97°C
- + Fixed water connection
- + Stainless steel 18/9
- + Marine voltages available
- + Can be supplied with different heating elements / power supplies




OPTIONS



- + To fix 2 swivel arms on the WKI.



- + No-drip tap at the front, swivel arm left, right, or both.



- + No-drip tap at the front, no swivel arm

MODEL	WKI 10n	WKI 20n 3kW	WKI 20n 6kW
Article number	9030110	9030115	9030120
Buffer stock hot water	10 ltr. / 80 cups	20 ltr. / 160 cups	20 ltr. / 160 cups
Hour capacity hot water	30 ltr. / 240 cups	30 ltr. / 240 cups	60 ltr. / 480 cups
Heating time 20 - 97°	24 min.	45 min.	23 min.
Tapping speed	6-9 sec./ltr.	6-9 sec./ltr.	6-9 sec./ltr.
Electrical connection	1N~220-240V/ 3.2kW/50-60Cy	1N~220-240V/ 3.2kW/50-60Cy	3N~380-415V/ 6.6kW/50-60Cy
Fuse 1N~220-240V	16A	16A	-
Fuse 3N~380-415V	-	-	3x10A
Fuse 1N~230V	-	3x20A	3x20A
Cold water connection	3/4"	3/4"	3/4"
Min. - Max. pressure	1-8 bar	1-8 bar	1-8 bar
Overflow connection	Ø15 mm	Ø15 mm	Ø15 mm
Cord length	1.3 m	1.3 m	1.3 m
Weight empty	8 kg	11 kg	11 kg
filled	19 kg	33 kg	33 kg

Marine executions	1N~110-120V/ 1.2kW/50-60Cy	1N~110-120V/ 1.2kW/50-60Cy	3~220V/ 6.6kW/50-60Cy
	1N~110-120V/ 2.4kW/50-60Cy	1N~110-120V/ 2.4kW/50-60Cy	3~380V/ 6kW/50-60Cy
	1N~110-120V/ 3.2kW/50-60Cy	1N~110-120V/ 3.2kW/50-60Cy	3~440V/ 6kW/50-60Cy
	2~380V/ 3kW/50-60Cy	2~380V/ 3kW/50-60Cy	
	3~440V/ 3kW/50-60Cy	3~440V/ 3kW/50-60Cy	

MODEL	WKI 40n
Article number	9030125
Buffer stock hot water	40 ltr. / 320 cups
Hour capacity hot water	90 ltr. / 720 cups
Heating time 20 - 97°	23 min.
Tapping speed	6-9 sec./ltr.
Electrical connection	3N~380-415V/ 9.6 kW/50-60Cy
Fuse 1N~220-240V	3x 16A
Fuse 3N~380-415V	3x 35A
Cold water connection	3/4"
Min. - Max. pressure	1-8 bar
Overflow connection	Ø15 mm
Cord length	1.5 m
Weight empty	17 kg
filled	61 kg

Marine executions	3~220V/ 9.6kW/50-60Cy
	3~380V/ 9kW/50-60Cy
	3~440V/ 9kW/50-60Cy

DIMENSIONS

	WKI 10n	WKI 20n 3KW	WKI 20n 6KW	WKI 40n
Art. No.	9030110	9030115	9030120	9030125
B1	188	253	253	316
B2	124	165	165	165
B3	74	165	165	165
D1	224	304	304	382
H1	523	583	583	685
H2	432	484	484	565
T1	249	313	313	404
T2	246	325	325	345

 Electrical connection |
  Water connection |
  Overflow connection

