

Animo offers a wide range of mobile serving combinations. With a ComBi-line flow water heater, you can prepare coffee and tea directly in containers on a serving trolley. No heavy lifting with containers or jugs. Our serving trolleys suit perfectly in every situation and offer enough space for your ingredients, cups and saucers, trash cans and rinsing baskets. Practical and flexible, coffee where you want it!

BENEFITS



CAPACITIVE TOUCH USER INTERFACE

- + Plug and play
- + Coffee dosing advice
- + Easy operator and service menu
- + Programmable timers
- + Day and total counters



HOT WATER DISPENSER

- + CB-W models have a hot water dispenser with no-drip tap in the brewing unit



TROLLEY CAFÉCRUISER ONE
(Max. 1 container, 20 l)



TROLLEY CAFÉCRUISER REGAL
(Max. 1 container, 20 l)



TROLLEY CAFÉCRUISER DE LUXE
(Max. 1 container, 20 l)

CB 5 / CB 5W		+		CB 10 / CB 10W		CB 20 / CB 20W	
CN5E		+		CN10E		CN20E	

ACCESSOIRES



SYNTHETIC FILTER HOLDERS

- + Light in weight
- + Heat insulated
- + Easy to handle



- + For making tea in a container, place the special tea filter with filler pipe.



- + S-swivelarm

MODEL	CB 5	CB 10	CB 20
Article number	1005393	1005401	1005409
CAPACITY COFFEE SYSTEM			
Brew time (water dosing time)	approx. 10 min./5 L	approx. 10 min./10 L	approx. 14 min./20 L
Hour capacity coffee/tea*	approx. 30 L, 240 cups	approx. 60 L, 480 cups	approx. 90 L, 720 cups
Electrical connection	1 N~220-240 V 3075 W, 50-60 Hz	3 N~380-415 V 6075 W, 50-60 Hz	3 N~380-415 V 9075 W, 50-60 Hz

* Flow of hot water

MODEL	CB 5W (Hot water)	CB 10W (Hot water)	CB 20W (Hot water)
Article number	1005397	1005405	1005413

CAPACITY COFFEE SYSTEM			
Brew time (water dosing time)	approx. 10 min./5 L	approx. 10 min./10 L	approx. 14 min./20 L
Hour capacity coffee/tea*	approx. 30 L, 240 cups	approx. 60 L, 480 cups	approx. 90 L, 720 cups

CAPACITY HOT WATER SYSTEM			
Boiler content	approx. 4,2 L	approx. 5,6 L	approx. 5,6 L
Water dispensing in 1 run	approx. 2,6 L	approx. 4,1 L	approx. 4,1 L
Hour capacity hot water	approx. 33 L	approx. 60 L	approx. 60 L
Heat up time (15-96°)	approx. 9 min.	approx. 9 min.	approx. 9 min.
Recovery time after 1.8L	approx. 6 min.	approx. 6 min.	approx. 6 min.
Electrical connection	1 N~220-240 V 3375 W, 50-60 Hz	3 N~380-415 V 6075 W, 50-60 Hz	3 N~380-415 V 9075 W, 50-60 Hz

* Flow of hot water

CONTAINER	CN5e	CN10e	CN20e
Article number	1005364	1005365	1005366
Content	5 L	10 L	20 L
Tap outflow height	130 mm	130 mm	130 mm
Holding temperature	approx. 80 - 85°C	approx. 80 - 85°C	approx. 80 - 85°C
Filter paper	Ø101/317	Ø152/457	Ø203/533
Electrical connection	1N~ 220-240 V/ 50-60 Hz / 50 W	1N~ 220-240 V/ 50-60 Hz / 100 W	1N~ 220-240 V/ 50-60 Hz / 100 W
Dimensions Ø x H mm	237 x 406	307 x 427	355 x 515

DIMENSIONS	CB 5	CB 10	CB 20	CB 5W	CB 10W	CB 20W
A =	235	235	235	235	235	235
B =	375	375	351	490	490	490
C =	725	820	920	725	820	920
D =	430	430	430	430	430	430
E =	641	733	835	641	733	835
F =				195	195	297
G =	126	126	126	126	126	126
H =	160	160	160	160	160	160
I =	77	77	77	77	77	77
J =	163	163	163	163	163	163
K =	96	96	96	96	96	96
L =	46	46	46	46	46	46

All dimensions in mm



MODEL	CAFÉCRUISER ONE	CAFÉCRUISER REGAL *	CAFÉCRUISER DE LUXE *
Article number	1012732	1012734	1012733
Dimensions W x D x H (mm)	662 x 638 x 1024	662 x 638 x 1024	662 x 638 x 1024
Top shelf (mm)	-	544 x 520	544 x 520
Distance between guides (mm)	-	137	137

* Excluding basket and stainless steel drip trays 510 x 510 mm