

Maintaining hot or cold beverages at a correct, constant temperature after preparation is essential for the preservation of flavour and quality. Animo manufactures an extensive range of drink and food containers for use in staff restaurants, hospitals, elderly homes etc. and for indoor and outdoor catering, transportation and service.

BENEFITS



NO-DRIP TAP

- + Content from 4 to 25 litres
- + No-drip tap
- + Brewing directly into the containers, preventing temperature and flavour loss



CONTAINER HEATING

- + CE containers have a heating element with klixon thermostat
- + CI containers have polyurethane insulations to min. temperature loss
- + CI containers are dishwasher proof



OPTIONS



- + Gauge glasses possible on CE models



- + Clip on lid



- + Tap protection



- + Container on a serving trolley

MODEL:	CE 4	CE 6	CE 8	CE 10	CE 20
Article number :	50050	50051	50052	50053	50056
Contents :	4 ltr., 32 cups	6 ltr., 48 cups	8 ltr., 64 cups	10 ltr., 80 cups	20 ltr., 160 cups
Electrical connection :	1N-220-240V, 165W, 50-60 Cy	1N-220-240V, 165W, 50-60 Cy	1N-220-240V, 165W, 50-60 Cy	1N-220-240V, 165W, 50-60 Cy	1N-220-240V, 385W, 50-60 Cy
Dimensions HxØ :	346 x 237 mm	405 x 237 mm	436 x 252 mm	489 x 252 mm	576 x 307 mm
Height incl. filter:	525 mm	590 mm	620 mm	675 mm	775 mm
Tap height :	120 mm	120 mm	120 mm	120 mm	120 mm
Holding temperature :	approx. 84-86°C	approx. 84-86°C	approx. 84-86°C	approx. 84-86°C	approx. 84-86°C
Weight empty :	4.4 kg	5.1 kg	7.5 kg	8 kg	11.5 kg
Weight full :	8.4 kg	11.1 kg	15.5 kg	18 kg	31.5 kg

MODEL:	CI 4	CI 6	CI 8	CI 10	CI 20
Article number :	50038	50039	50040	50041	50044
Contents :	4 ltr., 32 cups	6 ltr., 48 cups	8 ltr., 64 cups	10 ltr., 80 cups	20 ltr., 160 cups
Dimensions HxØ :	346 x 237 mm	405 x 237 mm	436 x 252 mm	489 x 252 mm	576 x 307 mm
Height incl. filter:	525 mm	590 mm	620 mm	675 mm	775 mm
Tap height :	120 mm	120 mm	120 mm	120 mm	120 mm
Temperature loss per hour :	5°C	4°C	4°C	3°C	3°C
Isolation :	Polyurethane CFK-free	Polyurethane CFK-free	Polyurethane CFK-free	Polyurethane CFK-free	Polyurethane CFK-free
Weight empty :	4.4 kg	5.1 kg	7.5 kg	8 kg	11.5 kg
Weight full :	8.4 kg	11.1 kg	15.5 kg	18 kg	31.5 kg

The Animo food containers have been especially designed for the safe storage and transport of hot and cold food. Due to the optimum insulation, temperature loss is minimal. For the heavy duty containers type MVC, the temperature loss is only 2-3 degrees per hour. Animo food containers are the solution for institutional kitchens, hospitals, staff restaurants, caterers and the armed forces.



MVC

+ The containers type MVC have been supplied to various army divisions and are provided with a NATO-stock number.



VC

MODEL:	MVC 5	MVC 10	MVC 15	MVC 20
Article number :	50070	50071	50072	50073
Contents :	5 ltr.	10 ltr.	15 ltr.	20 ltr.
Dimensions HxØ :	331 x 219 mm	323 x 292 mm	439 x 292 mm	380 x 356 mm
Weight :	6 kg	9 kg	10 kg	12 kg
Temperature loss per hour :	4°C	3°C	3°C	2.5°C

MODEL:	VC 4	VC 6	VC 8	VC 10
Article number :	50046	50047	50048	50049
Contents :	4 ltr.	6 ltr.	8 ltr.	10 ltr.
Dimensions HxØ :	220 x 238 mm	280 x 238 mm	310 x 252 mm	362 x 252 mm
Weight :	4 kg	5 kg	6 kg	7 kg
Temperature loss per hour :	4°C	4°C	3°C	3°C